

# Declaration of Performance

in accordance with Annex V of Regulation No. 305/2011

date of issue: 21.12.2016

revised: 10.09.2018



Number

**No. 1100\_004-CPR 2013 / 05 / 12**

Unique identification code of the product-type

**PAVAWALL**

Type, batch or serial number or other identifying mark to identify the construction product

**Batch N°. as shown on the label**

Intended use as foreseen by the manufacturer of the construction product in accordance with the harmonised technical specification

**Insulation for the building envelope**

Name, registered trade name or registered trade mark and contact address of the manufacturer

**Pavafrance SAS  
Route de la Pisciculture 37  
1701 Fribourg  
Switzerland**

Name and contact address of the authorised representative

**not relevant**

System for assessment and verification of constancy of performance of the construction product

**System 3**

**Notified body N° 0672**

**Otto-Graf-Institut Universität Stuttgart  
Forschungs- und Materialprüfungsanstalt (MPA)  
Pfaffenwaldring 4  
D-70569 Stuttgart**

**The notified certification body carried out the type testing under system 3.**

Declared performance

EN 13171:2012+A1:2015, Thermal insulating products for buildings - Factory made wood fibre (WF) products  
Intended use as foreseen by the manufacturer of the construction product in accordance with the harmonised technical specification

Title	Essential Characteristic	Performance	Test standard
Reaction to fire	4.2.6 Reaction to fire	E	
Release of dangerous substances	4.3.15 Release of dangerous substances	NPD (a)	
Sound absorption	4.3.12 Sound absorption	NPD	

# Declaration of Performance

in accordance with Annex V of Regulation No. 305/2011

date of issue: 21.12.2016

revised: 10.09.2018



## No. 1100\_004-CPR 2013 / 05 / 12

Sound absorption (for Flooring)	4.3.10 Dynamic stiffness	NPD	EN 13171:2012+A 1:2015
	4.3.11.1 Thickness dL	NPD	
	4.3.11.3 compressibility	NPD	
	4.3.13 Air flow resistance	AFr50	
Mouldering performance	4.3.17 mouldering	NPD	
Thermal resistance	4.2.1 Thermal resistance and thermal conductivity	$\lambda_d = 0.040 \text{ W/mK}$	
	4.2.3 Thickness	T5 / Siehe Etikette / voire étiquette / see label	
Short term water absorption	4.3.8 Water absorption	WS1.0	
Water vapour transmission	4.3.9 Water vapour transmission	MU3	
compressive strength	4.3.3 compressive strength	CS(10\Y)70	
	4.3.6 Point load	NPD	
Durability of the reaction to fire under the influence of heat, weather conditions and aging	4.2.7 Reaction to fire	NPD	
Durability of the Thermal resistance and thermal conductivity under the influence of heat, weather conditions and aging	4.2.1 Thermal resistance and thermal conductivity	NPD	
	4.3.2 Dimensional stability	NPD	
	4.3.2.2 Dimensional stability at 70°C	DS(70.-)2	
	4.3.2.2 Dimensional stability at specified temperature and humidity	NPD	
Tensile strength	4.3.5 Tensile strength parallel to faces	NPD	
	4.3.4 Tensile strength vertical to faces	TR7.5	
Durability of the compressive strength under the influence of aging	4.3.7 Long term compressive creep	NPD	
a) NPD = no Performance declared			

**Herbert Christen**

Technical Director

**Matthias Oelhafen**

Project Manager Certificates & Labels