

Declaration of Performance

in accordance with Annex V of Regulation No. 305/2011



date of issue: 11.06.2018

revised:

Number

No. 6207_004-CPR 2013 / 05 / 12

Unique identification code of the product-type

PAVATEX WDB

Type, batch or serial number or other identifying mark to identify the construction product

Batch N°. as shown on the label and on the product

Intended use as foreseen by the manufacturer of the construction product in accordance with the harmonised technical specification

Underlays for walls

Name, registered trade name or registered trade mark and contact address of the manufacturer

**Pavatex SA
Route de la Pisciculture 37
1701 Fribourg
Switzerland**

Name and contact address of the authorised representative

not relevant

System for assessment and verification of constancy of performance of the construction product

System 3

The notified body

N° 1390 CSI

approved the reaction to fire

The notified body

N° 1390 CSI

approved the resistance to water penetration

Declared performance

Products for buildings: Underlays for walls in accordance with the harmonised technical specification EN 13859-2

Title	Performance	Tolerance
Length [m]	50	-
Width [cm]	150 / 300	-
Resistance to passage of air [m ³ /m ² h]	NPD	-
Reaction to fire	E	-
Resistance to water penetration	W1	-
Resistance to water penetration after artificial ageing	W1	-
Specific weight [g/m ²]	100	±10
Water vapour transmission, sd-value [m]	0.02	±0.05
Maximum tensile force longitudinal / transverse [N/5cm]	220 / 140	±20%
Maximum tensile force longitudinal / transverse after artificial ageing [%]	190 / 120	±30%
Elongation longitudinal / transverse [%]	40 / 70	±50%
Elongation longitudinal / transverse after artificial ageing [%]	30 / 55	±50%
Tear resistance longitudinal / transverse [N]	80 / 90	±25%
Flexibility at low temperature [°C]	-20	-
Dimension stability longitudinal / transverse [%]	0.1 / 0.2	±0.05
Temperature resistance [°C]	-40 bis +80	-

Declaration of Performance

in accordance with Annex V of Regulation No. 305/2011

date of issue: 11.06.2018

revised:



No. 6207_004-CPR 2013 / 05 / 12

Hydrostatic pressure resistance [cmWS]	NPD	-
Resistance to driving rain	bestanden/ réussi/passed	-
Exposition to weather conditions [week]	12	-
NPD = no Performance declared		

A handwritten signature in blue ink, appearing to read 'H. Christen'.

Herbert Christen

Technical Director

A handwritten signature in blue ink, appearing to read 'M. Oelhafen'.

Matthias Oelhafen

Project Manager Certificates & Labels