

# Declaration of Performance

in accordance with Annex V of Regulation No. 305/2011



date of issue: 21.12.2016

revised:

Number

**No. 6207\_003-CPR 2013 / 05 / 12**

Unique identification code of the product-type

**PAVATEX FBA**

Type, batch or serial number or other identifying mark to identify the construction product

**Batch N°. as shown on the label and on the product**

Intended use as foreseen by the manufacturer of the construction product in accordance with the harmonised technical specification

**Underlays for walls**

Name, registered trade name or registered trade mark and contact address of the manufacturer

**Pavatex SA  
Route de la Pisciculture 37  
1701 Fribourg  
Switzerland**

Name and contact address of the authorised representative

**not relevant**

System for assessment and verification of constancy of performance of the construction product

**System 3**

**The notified body  
N° 0432 MPA Erwitte  
approved the reaction to fire**

**The notified body  
N° 0799 TBU Greven  
approved the resistance to water penetration**

Declared performance

Products for buildings: Underlays for walls in accordance with the harmonised technical specification EN 13859-2

Title	Performance	Tolerance
Length [m]	50	-
Width [cm]	150	-
Resistance to passage of air [m <sup>3</sup> /m <sup>2</sup> h]	NPD	-
Reaction to fire	E	-
Resistance to water penetration	W1	-
Resistance to water penetration after artificial ageing	W1	-
Specific weight [g/m <sup>2</sup> ]	200	-10/+30
Water vapour transmission, sd-value [m]	0.02	±0.05
Maximum tensile force longitudinal / transverse [N/5cm]	270 / 230	±20%
Maximum tensile force longitudinal / transverse after artificial ageing [%]	250 / 210	±30%
Elongation longitudinal / transverse [%]	35 / 35	±15%
Elongation longitudinal / transverse after artificial ageing [%]	28 / 28	±12%
Tear resistance longitudinal / transverse [N]	110 / 110	±20%
Flexibility at low temperature [°C]	-25	-
Dimension stability longitudinal / transverse [%]	0.1 / 0.2	±0.05
Temperature resistance [°C]	-40 bis +80	-

# Declaration of Performance

in accordance with Annex V of Regulation No. 305/2011



date of issue: 21.12.2016

revised:

## No. 6207\_003-CPR 2013 / 05 / 12

Hydrostatic pressure resistance [cmWS]	NPD	-
Resistance to driving rain	bestanden/ réussi/passed	-
Exposition to weather conditions [week]	12	-
NPD = no Performance declared		

Handwritten signature of Albert Beeler in blue ink.

**Albert Beeler**

Head Technology Center

Handwritten signature of Matthias Oelhafen in blue ink, with a faint circular stamp in the background.

**Matthias Oelhafen**

Project Manager Certificates & Labels