



- Long-term elastic adhesive with high adhesive strength
- Can also be used at cold temperatures
- Suitable for gluing connections on dry clean substrates

Delivery form

	Contents per container (ml/ g)	Box contents [units]	Accessories included
Cartridge	310	20	20 snap-off nozzles

Field of application



Technical data

Material	Dispersion adhesive
Minimum installation temperature for base and air [°C]	frozen over, air -10
Installation temperature	
Primer [°C]	-10 to +50
Temperature resistance [°C]	-20 to +80
Tight after [h]	depending on absorbency of substrate 2-12

Usage guidelines*

	ml/m	Bead	Cartridge yield
PAVATEX membranes	20	5 mm	~ 15 m
	40	7 mm	~ 7.5 m
Gluing membrane/membrane = 5 mm bead			
Gluing membrane/bare substrate = 7 mm bead			

* no joints or penetrations

Product description

For making airtight connections of vapour-barrier and airtight membranes of all types on dry and clean substrates. The adhesive connections meet the requirements of the applicable norms DIN 4108-7, SIA 180 and ÖNORM B 8110-2.

The adhesive power is very high, with fast drying. No pressure plate is required on load-bearing substrates. The adhesive can also be used at cold temperatures.

Adhesion trials are essential for materials that are not described in the application note.

You can find details on applications and installation guidelines in the technical or sealing brochure.

Storage

Store dry and protected from sunlight. Can also be stored in frosty conditions.

Shelf life

24 months unopened

Note on working safety

Before use read the identification label. Contains ethanol. Ensure good ventilation and avoid contact with sources of ignition.

PAVATEX system guarantee

The high-performance adhesion and gluing components used in the PAVATEX system solutions ensure long-lasting, reliable system sealing in modern, multifunctional building envelopes - now also guaranteed by the new PAVATEX warranty. It offers comprehensive service if damage occurs, and therefore once again increases security for designers, installers and builders.

