



- For sealing inside and outside, for rendering and can be painted over
- Humidity-regulating with variable S_d value
- Suitable for renovation and new builds

Delivery form

	Box weight [kg]	Roll length [m]	Roll width [mm]	Box contents [units]
PAVAFIX WIN	4.0	25	90	4

Field of application



Technical data

Material	PET fleece and PA foil
Thickness [mm]	0.65 mm
Minimum installation temperature for base and air [°C]	frozen over, air -5
Installation temperature Tape [°C]	-5 to +40
Temperature resistance [°C]	-40 to +80
For rendering	yes
Resistance to water penetration	W1
UV weathering stability	3 months

Product description

For sealing connection joints in windows, doors and interior construction panel PAVAROOM to the adjacent building part. The humidity-regulating tape can be used for interior and exterior sealing, and so avoids installation errors. The joint remains dry all year round, so damage from condensation can be effectively prevented.

With its high-performance adhesive surface, the tape is suitable for applying directly to the frame and the adjacent smooth masonry.

You can find details on applications and installation guidelines in the technical or sealing brochure.

Storage

Cool and dry, protected from sunshine.

PAVATEX system guarantee

The high-performance adhesion and gluing components used in the PAVATEX system solutions ensure long-lasting, reliable system sealing in modern, multifunctional building envelopes - now also guaranteed by the new PAVATEX warranty. It offers comprehensive service if damage occurs, and therefore once again increases security for designers, installers and builders.

