



- High adhesive strength, stable shape, cannot be over-stretched
- Colour matched to the facade membrane
- Withstands three months of exposure to the weather

Delivery form

	Box weight [kg]	Roll length [m]	Roll width [mm]	Box contents [units]
PAVAFIX 60	2.8	25	60	4
PAVAFIX 20_40	2.8	25	60	4
PAVAFIX 150	3.2	25	150	2

Field of application



Technical data

Material	Pure acrylic adhesive on a plastic carrier
Thickness [mm]	0.3
Minimum installation temperature for base and air [°C]	-5
only with PAVAPRIM [°C]	-10
Installation temperature Tape [°C]	-5 to +40
Temperature resistance [°C]	-40 to +90

Product description

PAVAFIX is an all-round acrylate adhesive tape for permanent sealing of PAVATEX membranes and wood-fibre boards indoors and outdoors. Very high adhesion and good resistance to ageing and water. Can be exposed to the weather for max. 3 months. When gluing to porous or mineral contact surfaces, a preliminary coating of PAVABASE or PAVAPRIM is always applied.

PAVAFIX 60:	For gluing foils
PAVAFIX 20_40:	For gluing connections
PAVAFIX 150:	For bonding ridge, valley, edge and board joints

You can find details on applications and installation guidelines in the technical or sealing brochure.

Storage

Cool and dry, protected from sunshine.

PAVATEX system guarantee

The high-performance adhesion and gluing components used in the PAVATEX system solutions ensure long-lasting, reliable system sealing in modern, multifunctional building envelopes - now also guaranteed by the new PAVATEX warranty. It offers comprehensive service if damage occurs, and therefore once again increases security for designers, installers and builders.

