



- Double-sided, high adhesive force, high initial adhesion
- Suitable for rough and smooth surfaces
- Fast and secure gluing of connections without drying time

**Delivery form**

	Box weight [kg]	Roll length [m]	Roll width [mm]	Box contents [units]
PAVATAPE 12	2.0	10	12	3

**Field of application**



**Technical data**

Material	Double-sided butyl rubber tape with thread inlay	
Thickness [mm]	3.5	
Minimum installation temperature for base and air [°C]	+5	
only with PAVAPRIM [°C]	-10	
Installation temperature Tape [°C]	+5 to + 30	
Temperature resistance [°C]	-40 to + 100	

**Product description**

Solvent-free and elastic airtight seal of butyl rubber. The durable seal is suitable for connecting all types of vapour barrier according to SIA 180 and DIN 4108-7. Also usable for water-tight bonding of roofing membranes.

You can find details on applications and installation guidelines in the technical or sealing brochure.

**Storage**

Cool and dry, protected from sunshine.

**PAVATEX system guarantee**

The high-performance adhesion and gluing components used in the PAVATEX system solutions ensure long-lasting, reliable system sealing in modern, multifunctional building envelopes - now also guaranteed by the new PAVATEX warranty. It offers comprehensive service if damage occurs, and therefore once again increases security for designers, installers and builders.

