



- Windtight and watertight sarking lining for sarkings with exceptional performance above 5° roof pitch
- Easy to weld seamlessly and homogeneously, with solvent welding agent or hot air
- Matching system accessories incl. PAVATEX system guarantee

Delivery form

Roll width [m]	Roll length [m]	Roll area [m ²]	Roll weight [kg]
1.5	50.0	75.0	25

Field of application



Technical data

Material	Polyester non-woven fabric with TPU coating	
s _d value [m]	0.18	
Specific weight [g/m ²]	330	
Waterproofing	W1	
Temperature resistance [°C]	-40 to +80	
Fire behaviour (EN 13501-1)	Class E	
Stretch [%]	lengthwise	50
	across	70
Maximum tensile force [N/5cm]	lengthwise	300
	across	350
Resistance to tearing (nail shank) [N]	lengthwise	200
	across	200
CE	EN 13859-1	

Product description

PAVATEX UDB, the vapour-permeable, hot or cold weldable sarking lining for sarkings with exceptional performance above 5° roof pitch.

A homogeneous and insoluble seam joint can be made easily using UDB solvent welding agent or using hot air.

Storage

Store the rolls dry and cool, lying down or upright, protected from sunshine and humidity.



PAVATEX System accessories

- UDB strip
- UDB solvent welding agent
- UDB brush bottle
- UDB sleeve
- PAVAFIX SN BAND

You will find details on usage and installation guidelines in the sealing brochure.

