




- Woodfibre insulation block suitable for rendering for the modernisation of solid walls
- Convenient format for simple, fast installation
- There are diverse render systems approved under the building regulations of the various countries

Delivery form

Thickn. [mm]	Weight [kg/sqm]	Weight [kg/Block]	Format [cm]	Number of blocks / pallet	per pallet [sqm]	per pallet [kg]	Edge profile
120	15.6	3.8	60 x 40	54	13.0	217	Flat
140	18.2	4.4	60 x 40	48	11.5	225	Flat
160	20.8	5.0	60 x 40	42	10.1	225	Flat
180	23.4	5.6	60 x 40	36	8.6	217	Flat
200	26.0	6.2	60 x 40	30	7.2	202	Flat
220	28.6	6.9	60 x 40	30	7.2	221	Flat

Production plant: Golbey, France

Field of application



PAVATEX soffit board

Thickn. [mm]	Weight [kg/sqm]	Format [cm]	Number of boards/package	Number of boards / pallet	per pallet [sqm]	per pallet [kg]	Edge profile
20	3.7	110 x 60	8	96	63.4	249	Flat
40	7.4	110 x 60	4	48	31.7	249	Flat

Production plant: Cham, Switzerland

Technical data

Bulk density ρ [kg/m ³]	130
Thermal conductivity (EN 13171) λ_p [W/(mK)]	0.040
Specific heat capacity c [J/(kgK)]	2100
Vapour diffusion resistance coefficient μ	3
Fire behaviour (EN 13501-1)	Class E
Compressive stress at 10% compressive deformation [kPa]	70
Tensile strength perpendicular to plane of board [kPa]	7.5
Waste code according to The European Waste Catalogue (EWC)	030105; 170201; 170604
Identification code	WF-EN13171-T5-DS(70.-)2-CS(10/Y)70-TR7.5-WS1.0-MU3-AFr100
KEYMARK	011-7D020

Product description

PAVAWALL-BLOC heat-storing insulation block is a render base board for thermal insulation composite systems. It is ideally suited to the modernisation of existing buildings as well as for new constructions. From manufacture through to disposal, PAVAWALL-BLOC satisfies all ecological requirements. It offers a high thermal storage capacity and outstanding heat protection in the summer. The raw material for PAVAWALL-BLOC is natural softwood waste material generated by sawmills. PAVAWALL-BLOC offers an outstanding substrate for the adhesion of subsequent render layers. Rendering advice is available on request.

Full declaration

For further information see MSDS on www.pavatex.com

Storage

Store dry and protected from damage. Only install when dry. Stack no more than 4 pallets on top of each other.

