


UDB strip



- Welding strip coated both sides with polyurethane for weldable sarking lining, hot or cold weldable
- Ideal for binding battens into the uniformly welded whole area
- Multifunctional uses for detail solutions and joints

Delivery form

Field of application

Roll width [m]	Roll length [m]	Roll area [m ²]	Roll weight [kg]	Box contents [units]
0.3	25.0	7.5	3	5

Technical data

Material	Polyester Faservliesstoff mit TPU Beschichtung		
s _d value [m]	0.18		
Specific weight [(g/m ²)]	330		
Waterproofing	W1		
Temperature resistance [°C]	-40 to +80		
Fire behaviour (EN 13501-1)	Class E		
Can be exposed to the weather for (months)	3		
Stretch [%]	lengthwise	50	
	across	70	
Maximum tensile force [N/5cm]	lengthwise	300	
	across	350	
Resistance to tearing (nail shank) [N]	lengthwise	200	
	across	200	

Storage

Store the rolls dry and cool, lying down or upright, protected from sunshine and humidity.

UDB solvent welding agent



- Fast and effective working and welding of joints
- Gives a homogeneous and insoluble seam joint
- Very fast reaction time when welding

Delivery form

Material	Content of can [l]	Box contents [cans]	Shelf life [months]
Tetrahydrofuran 99.9 %	1.0	6	18

Storage

Storage class 3, VbF (German flammable liquids regulation) class B. Store original container tightly sealed, dry, cool and frost-free away from direct sunlight.

Minimum working temperature: 5°C. Carefully close opened containers and use immediately.

See safety data sheet at www.pavatex.com

UDB brush bottle



- Empty PE bottle with screwed-on brush head
- Simple and efficient application of the solvent welding agent
- Ideal rate of application of the solvent welding agent

Delivery form

Version	Value
Material	Transparent plastic bottle with brush applicator
Capacity	0.5 l
Box contents	1 pcs

Storage

dry and cool, protected from sunlight and humidity.

UDB sleeve



- Ready-made shaped piece, specially for rapid air, wind and watertight connection of pipe penetrations
- Easy connection of standard pipe diameters from DN 90 to DN 125
- The long-term elastic stretchability of up to 600% enables trouble-free compensation of the usual building movements

Delivery form

Version	Value
Box contents	10 pcs
Weight	80 g
Overall height	100 mm
Wall thickness	0.8 mm
Outside diameter:	255 mm
Largest internal diameter	135 mm
Smallest internal diameter	85 mm
Stretch, lengthwise	600 %
Stretch, across	600 %

Storage

dry and cool, protected from sunlight and humidity.